

Oil Pattern Distance	43	Reverse Brush Drop	38	Oil Per Board	50 ul
Forward Oil Total	19.15 mL	Reverse Oil Total	15.35 mL	Volume Oil Total	34.5 mL
Tank Configuration	A Only	Tank A Conditioner	KEGEL	Tank B Conditioner	KEGEL

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	14	74	0.0	1.9	1.9	3700
2	7L	7R	3	14	81	1.9	7.8	5.9	4050
3	7L	7R	3	18	81	7.8	15.4	7.6	4050
4	10L	10R	3	18	63	15.4	23.0	7.6	3150
5	10L	10R	2	22	42	23.0	29.2	6.2	2100
6	10L	10R	2	22	42	29.2	35.4	6.2	2100
7	2L	2R	0	22	0	35.4	43.0	7.6	0


	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	0	43.0	38.0	-5.0	0
2	10L	10R	3	18	63	38.0	30.4	-7.6	3150
3	10L	10R	2	18	42	30.4	25.3	-5.1	2100
4	10L	10R	2	14	42	25.3	21.4	-3.9	2100
5	10L	10R	2	14	42	21.4	17.5	-3.9	2100
6	7L	7R	2	10	54	17.5	14.7	-2.8	2700
7	7L	7R	1	10	27	14.7	13.3	-1.4	1350
8	2L	2R	1	10	37	13.3	11.9	-1.4	1850
9	2L	2R	0	10	0	11.9	0.0	-11.9	0

Cleaner Ratio Main Mix                      NA      Forward

Cleaner Ratio Back End Mix                NA      Reverse

Cleaner Ratio Back End Distance        NA      Combined

Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle:Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5.83	1.3	1	1	1.3	5.83

